

VERSA-DRILL MARK70

AIR ROTARY, WATER WELL, GEOTHERMAL, EXPLORATION, CATHODIC PROTECTION



VERSA-DRILL MARK70

70,000 LBS PULLBACK

STANDARD FEATURES AND SPECIFICATIONS

CARRIER

Peterbilt 367 6x4 Cummins ISX with 605 HP 13-speed transmission. 60-gal ON road/150-gal OFF road fuel tanks

TRANSFERCASE

Fabco Automotive Covered under Peterbilt powertrain warranty

HYDRAULIC SYSTEM

Bosch Rexroth

TOP HEAD

Variable 3-speed/torque with 2.4" thru-hole 0-125 rpm @ 8,100 lbf·ft 0-175 rpm @ 5,840 lbf·ft 0-250 rpm @ 3,545 lbf·ft

DERRICK & FEED SYSTEM

26' top head travel 70,000 lbs pullback 28,000 lbs pulldown 158 FPM up 235 FPM down

ROD HANDLING

4.5"x20' - 25 rod automated 3.5"x20' - 15 rod carousel/15 rod box 4.5"x20' - 11 rod carousel/9 rod box

MAIN WINCH

18,000 lb.

CONTROL PANEL

Electric over hydraulic controls Marine grade electric switches Hydraulic joysticks 4" engine display Twin aluminum platforms Aluminum console cover

LEVELING JACKS

Two 36" stroke independently controlled Two 48" stroke independently controlled

NIGHT LIGHTS

8 LED night lights

TOOL BOXES

14"x12"x24" 24"x24"x30"

OVERALL DIMENSIONS

Length: 40' Width: 8.5' Derrick up height: 44' Derrick down height: 13'4"

OPTIONS (at additional cost)

MAIN WINCH

25,000 lb

AUXILIARY WINCH

4,000 lb. 8,000 lb. Free fall options available

MUD PUMP

4x3x13 centrifugal 425 gpm/300 psi 5x6 piston 200 gpm/310 psi (skid mounted) 5.5x8 piston 317 gpm/338 psi (skid mounted)

AIR COMPRESSOR

500 cfm/200 psi Vanair 600 cfm/250 psi Vanair 1070 cfm/350 psi Doosan

LINE OILER

7-gallon venturi

WATER INJECTION

25 gpm FMC 75 gpm American Mfg Company Foam pulse pump

ADDITIONAL OPTIONS

0-50 gpm/5,000 psi auxiliary hydraulics TIREBOSS[™] tire pressure control system In-deck grouter (multiple options) Hose reel (multiple options) Aluminum catwalk Remote pendant for winches & jib boom Versa-Rod spinner 1-2-3 slot hammer holder Stabilizer bushings 300-gallon mud pit assembly The MUD MANAGER solids control system Cribbing rack

